



PRODUCT OVERVIEW

Product type:

- ✓ Primer powder coatings available in two grades: epoxy or epoxy-polyester.

Benefits:

- ✓ Features excellent adhesion with solvent-based topcoats and supports a variety of topcoat options.
- ✓ Allows for non-sanding reapplication, offering durable and aesthetically pleasing paint specifications with high work efficiency.

Usage:

As a primer powder coating, it enhances adhesion with topcoats suitable for various applications.

Main features:

Designed for high weather resistance coating specifications using epoxy resin grade.

Designed for general coating specifications using epoxy-polyester resin grade.

Non-sanding topcoat application possible.

Compatible with various topcoats: melamine baking, acrylic baking, single-component and two-component urethane paints, fluoropolymer baking, and topcoat powder coatings.

Coating specification:

Pre-treatment: Appropriate substrate preparation.

Painting method: Electrostatic spray.

Curing Condition: High weather-resistance grade: 180°C for 20 minutes.

General grade: 160°C for 20 minutes.

Product specification:

Paint form: Powder

Color: High weather-resistance grade: Ivory (5Y9/1)

General grade: Ivory (2.5Y9/1), Light Gray (N-7.7)

Contact information:

- ✓ Distributed by: COATURE VIET NAM CO.,LTD.
- ✓ Email: info@coaturevn.com.
- ✓ Website: <http://coaturevn.com>.
- ✓ Phone: Da Nang office: +84(0)987 388 887/ +84(0)762 871 449.
Ha Noi office: +84(0)858 242 215.