



PRODUCT OVERVIEW

Product type:

- ✓ Two-component epoxy primer with strong solvent resistance.

Benefits:

- ✓ Lifting resistance (withstands strong solvents of Japanese coatings).
 - ✓ High adhesion to steel.
 - ✓ Chemical resistance / seawater resistance.
 - ✓ Easy to sand (for finishing coats).
 - ✓ Pot-life stable even at 35°C.
-

Usage:

Application for steel/metal products.
Metal processing details.
Coordinate with Japanese finishing paint.

Main Features:

Easy to apply with a film thickness of 30–40 µm, Thin film thickness (30µm) is closest to Japanese standard. Solves the long-standing problem of "too thick film causing error".
Has excellent corrosion resistance and very good adhesion to steel surfaces..
Excellent chemical resistance, water resistance and waterproofing.

Instructions:

Pre-treatment: Shot blasting according to ISO standard–Sa2½ (SSPC–SP10).
Painting method: Roller/Roll – Airless Paint Gun – Airless Spray Gun
Curing conditions: Drying time (ambient temperature): 20°C × 1 hour; 30°C × 30 minutes. / Hardening time: 20°C × 8 hours; 30°C × 4 hours.

Product Information:

Paint type: 2 components.
Color: White, light gray.
Epoxy standard solvent.

Contact information:

- ✓ Distributed by: COATURE VIETNAM CO., LTD.
- ✓ Email: info@coaturevn.com
- ✓ Website: <http://coaturevn.com>
- ✓ Phone : Danang Office: +84(0)987 388 887
Hanoi Office: +84(0)987388887